

## Standard LED remote indicator panel



**Part-No.: 764790**

**Approval: VdS**

Additional indicator for up to 32 alarm, trouble or collective signals. Connection via an integrated 32-pin terminal strip. The indicator is controlled via relay contacts or semiconductor outputs with positive-guided contacts in the hazard detection system. With key for lamp testing, integrated buzzer and easy-to-maintain terminal card. Elegant plastic housing for surface mounting.

|                             |                                                               |
|-----------------------------|---------------------------------------------------------------|
| Operating voltage           | 10 ... 15 V DC                                                |
| Quiescent current @ 12 V DC | approx. 1 mA                                                  |
| Alarm current @ 12 V DC     | approx. 380 mA (incl. 32 LED & buzzer)                        |
| Display                     | 32 LED, red                                                   |
| Connection terminal         | max. 1.5mm <sup>2</sup>                                       |
| Ambient temperature         | -5 °C ... 50 °C                                               |
| Storage temperature         | -25 °C ... 75 °C                                              |
| Air humidity                | < 95 %                                                        |
| Type of protection          | IP 40                                                         |
| Housing                     | ABS plastic                                                   |
| Color                       | white (similar to RAL 9003), front blue (similar to RAL 5003) |
| Weight                      | approx. 1000 g                                                |
| Dimensions                  | W: 270 mm H: 221 mm D: 71 mm                                  |



This indicator panel is not suitable for application as an initial warning device for the fire brigade.