

Remote indicator for Series 9000 / ES Detect, red lens



Features:

- 4 pulsed LEDs
- Power-saving compact indicator
- Viewing angle 180°

Part-No.: 781804

Red prism is illuminated by 4 pulsed LEDs to optimize energy consumption. Connection by 3/4 wire cable to detector base.

Common technical data

Operating voltage	6 ... 12 V DC
Quiescent current @ 12 V DC	approx. 0,005 mA
Alarm current	approx. 9 mA @ 12 V DC
Frequency of flash	1,5 Hz
Ambient temperature	-25 °C ... 70 °C
Storage temperature	-35 °C ... 85 °C
Air humidity	< 95 %
Type of protection	IP 42
Housing	ABS plastic
Color	white, similar to RAL 9010
Weight	approx. 60 g
Dimensions	W: 85 mm H: 82 mm D: 27 mm

 Operation only with conventional automatic fire detectors Series 9000 and standard detector base Part No. 781590. Detectors Series ES Detect: Detector base 805590 required. Max. 4 indicators per detector / max. 3 detectors per indicator. Max. 4 detector per indicator per detector zone. Detector Series 9000: Adapter module (Part No. 781487) required. Max. 3 indicators per detector / max. 3 detectors per indicator. Max. 60 remote indicators per zone (with max. 20 detectors) each additional detector, decrease 3 remote indicators (e.g. 21 detectors -> max. 57 remote indicators 30 detectors -> max. 30 remote indicators)