

## Multi-stimulus detector tester TF 1001



### Part-No.: 805550

Same as 805551, but for testing of detectors with smoke and heat sensors. For testing CO consider multi-stimulus detector tester TF 2001 (Part No. 805551).

### Common technical data

Battery charging	75-90 minutes
Heat detector response threshold	up to 90°C adjustable up to 100°C
Application temperature	5 °C ... 45 °C
Storage temperature	-10 °C ... 50 °C
Air humidity	< 85 %

### Features:

- Creation of smoke and heat with one single test device
- Desmoking of detector via an integrated fan for fast resetting
- Simultaneous or successive testing with different activating materials
- Suitable for single and multi-criteria detectors
- Suitable for smoke and heat detectors
- Targeted heat radiation facilitates quick activation of the thermal sensors (up to 90°C/194°F and/or can be switched up to 100°C/212°F)
- Test activation through infrared barrier, no mechanical triggering, ceiling contact not necessary
- Quick, easy and efficient testing since there is no need to exchange test device
- Multilingual and user-friendly menu
- Portable battery-powered device
- Environmentally friendly and safe through usage of test cartridges instead of test gas cans



Please see our website for latest edition of the safety data sheet. Due to its nature, this article contains components classified as dangerous goods. Please clarify in advance with your forwarding agent if he accepts the transport of dangerous goods and if necessary observe the import regulations. The dangerous goods class for road transport or air transport is as follows: UN-No. UN3496 ADR-Class 9



Detector tester kit TF 1001 consists of: Testing head, smoke capsule, 2 Ni-MH battery packs, charger

### Accessories:

805552	Smoke capsule for multi-stimulus detector tester 805550/51
805553	CO capsule for multi-stimulus detector tester 805551 (Testifire TC3)
060426	Plastic telescopic extension
060427	Plastic telescopic rod
060431.10	Spare battery baton
805543.10	Solo Universal Fast Battery Charger SOLO 727