

Display and operating unit for rack, 7 HU



Part-No.: FX808324.19


Same as FX808324, but for rack installation. Operating unit front, including tilting assembly frame for display and operation of the FACP or a fire alarm system.


HMI (Human Machine Interface) with capacitive keys and backlit status displays for intuitive operation in the event of a change of status.

Operating release through access codes for all levels, with menu-driven display at different operating levels.

- Capacitive keyboard for touch sensitive operation
- Program-controlled night design with interactive keyboard menu
- Four access levels via access codes (details can be found in technical manual)
- Four freely programmable function keys on each access level with operating macros for supplementary functions
- 5.7" monochrome display

Operating voltage	24 V DC
Quiescent current	approx. 156 mA
Resolution	320 x 240 pixel
Ambient temperature	-5 °C ... 45 °C
Air humidity	< 95 % (non condensing)
Type of protection	IP 30
Color	light grey, similar to RAL 7035
Color front plate	black, similar to RAL9005
Weight	approx. 1 kg
Dimensions	W: 450 mm H: 320 mm D: 30 mm

 Please note: To save valuable resources, installation and operating instructions are included in different languages on a USB storage device and only a paper short operating instruction and the logbook will continue to be included.

 Labeling sets included: Bulgarian, Chinese simplified, Chinese traditional, Croatian, Czech, Danish, Dutch (Netherlands), English (International), English (FM), English/Arabic, Flemish (Belgium), French (France), French (Switzerland), German (Austria), German (Germany), German (Switzerland), Greek, Hungarian, Italian, Polish, Portuguese, Romania, Russian, Slovakian, Slovenian, Spanish, Turkish, Walloon (Belgium)